

SAFETY DATA SHEET MAXIMUS HD 10W-40

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MAXIMUS HD 10W-40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

Uses advised against

This product must not be used outside of the practices recommended in Section 1 without

prior advice from the supplier.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFISI A.Ş.

Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ Istanbul

Tel: +90 850 339 1919 Fax: +90 216 275 3854 madeniyag@petrolofisi.com.tr

Contact person Customer Services: madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Customer Services: 0850 339 1919 (working hours)

National emergency telephone Emergency Medical Services: 112 National Poison Consultance Center: 114

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains Calcium sulfonate (polymer). May produce an allergic reaction.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Revision date: 08/04/2022 Revision: 2 Supersedes date: 17/06/2011

MAXIMUS HD 10W-40

Madeni yağlar (petrol), C15-30, hidrojen ile işlem görmüş nötr

60-80%

baz yağ

CAS number: 72623-86-0 EC number: 276-737-9

REACH registration number: 01-

2119474878-16-0001

Classification

Not Classified

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY

25-40%

PARAFFINIC; BASEOIL - U (DMSO <%3 by IP 346)

Classification
Not Classified

Phosphorodithioic acid <1%

CAS number: — EC number: 283-392-8

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411

Calcium sulfonate (polymer) <1%

CAS number: 70024-69-0 EC number: 274-263-7

Classification

Skin Sens. 1 - H317

p-dodecylphenol <1%

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments Some substances are not classified by legistlation. They are self classified by the

manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Revision date: 08/04/2022 Revision: 2 Supersedes date: 17/06/2011

MAXIMUS HD 10W-40

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation No specific symptoms known.

Ingestion No specific symptoms known.

Skin contact No specific symptoms known.

Eye contact No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use the following: Water.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove

from the area as soon as possible.

6.4. Reference to other sections

SECTION 7: Handling and storage

MAXIMUS HD 10W-40

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational

exposure limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking

and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

When using do not eat, drink or smoke.

Respiratory protectionNo specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Yellow.

Flash point 226°C OC (Open cup).

Relative density 0.86g/ml @ 15°C

Viscosity 13.3 cSt @ 100°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Revision date: 08/04/2022 Revision: 2 Supersedes date: 17/06/2011

MAXIMUS HD 10W-40

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product is immiscible with water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

MAXIMUS HD 10W-40

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

SECTION 16: Other information

Key literature references and

This SDS is prepared based on the information received from suppliers.

sources for data

Revision comments Revised classification.

Issued by Sena Ezgi SELÇUK Safety Data Sheet Specialist (Certificate No: GBF01.55.06 02.10.2024)

Revision date 08/04/2022

Revision 2

Supersedes date 17/06/2011

SDS number 10350

MAXIMUS HD 10W-40

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains Calcium sulfonate (polymer). May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.