



SAFETY DATA SHEET

MAXIMUS SUPER DIESEL 20W-50

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MAXIMUS SUPER DIESEL 20W-50

Product number 11345

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

Uses advised against This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. This product is designed only to suit automotive applications and no provision is made for the requirements of aviation applications.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFİSİ A.Ş.
Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ İstanbul
Tel: +90 850 339 1919
Fax: +90 216 275 3854
madeniyag@petrolofisi.com.tr

Contact person Customer Services: madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Customer Services: 0850 339 1919 (working hours)

National emergency telephone number Emergency Medical Services: 112 National Poison Consultance Center: 114

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

Environmental The product is mildly toxic to aquatic organisms.

2.2. Label elements

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.
P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

MAXIMUS SUPER DIESEL 20W-50

As supplied, the material does not present a health hazard.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Distillates (petroleum), hydrotreated heavy paraffinic 80-95% CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-2119484627-25-0033
Classification Not Classified
Mineral Oil 1-5% CAS number: 64742-55-8
Classification Not Classified
Mineral oil (mixture) 1-5% CAS number: —
Classification Not Classified
Calcium long chain alkylphenate sulphide <1% CAS number: 122384-87-6
Classification Aquatic Chronic 4 - H413
Zinc dialkyl dithiophosphate <1% CAS number: 68649-42-3 EC number: 272-028-3
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411
Alkaryl amine <1% CAS number: 36878-20-3 EC number: 253-249-4
Classification Aquatic Chronic 4 - H413

MAXIMUS SUPER DIESEL 20W-50

Phenol-4-dodecyl		<1%
CAS number: 104-43-8	EC number: 203-202-9	
M factor (Acute) = 10	M factor (Chronic) = 10	
Classification		
Skin Corr. 1C - H314		
Eye Dam. 1 - H318		
Repr. 1B - H360		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

Composition comments	Some substances are not classified by legislation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%
Ingredient notes	If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, the registration date has not yet come due or this information is proprietary.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific treatment. Treat symptomatically.
Specific treatments	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

MAXIMUS SUPER DIESEL 20W-50

Suitable extinguishing media The product is not flammable. Extinguish with the following media: Foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition may produce smoke, oxies of carbon and lower molecular weight organic compounds whos composition have not been characterised.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide (CO). A complex mixture of airborne solids, liquids and gases can be released.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

For non-emergency personnel Necessary precautions should be taken to ensure that non-educated personnel do not intervene.

For emergency responders Wear protective clothing as shown in section 8 of this safety data sheet. Notification: In case of spillage, notify the local authorities as appropriate or as necessary. Stop the leakage source if it can be done without risk. Limit spillage to prevent further contamination of soil, surface or ground water. Remove any spilled material as soon as possible by following the precautions in the section Exposure Controls / Personal Protection. Use suitable techniques such as non-flammable absorbent materials or pumping. When possible or appropriate, remove the contaminated soil from the area. Place contaminated products in disposable boxes and dispose of in accordance with regulations. If a heated material is spilled, allow it to cool before handling with disposal methods.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 1 for emergency contact information. For waste disposal, see Section 13. See Section 7 for more information on safe handling. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Provide adequate ventilation.

MAXIMUS SUPER DIESEL 20W-50

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Avoid breathing vapors / mist. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store away from incompatible materials (see Section 10). Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep only in the original container. Protect from freezing and direct sunlight.

Storage class

Chemical storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

The product must be used as specified in the data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

Oil mist: TWA: 5 mg/m³ (ACGIH). In no case should this limit be exceeded or the local limit, if it is more restrictive.

Mineral Oil

Mineral oil - Inhalable fraction: TWA: 5 mg/m³, US. ACGIH Threshold Limit Values (03 2014)

Mineral oil (mixture)

Mineral oil: TWA: 5 mg/m³, 8 hours [EH-40 MEL, (Europe, 2002)]

Ingredient comments

WEL = Workplace Exposure Limits

Biological limit values

No information available.

DNEL

No information available.

DMEL

No information available.

PNEC

No information available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

The effectiveness of personal protective equipment, together with other elements, depends on the degree of ventilation. Depending on the particular situation in question, Get professional support.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Nitrile rubber. Polyvinyl chloride (PVC).

MAXIMUS SUPER DIESEL 20W-50

Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.
Thermal hazards	If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Odour	Odorless or slightly petroleum oil
Odour threshold	No specific test data are available.
pH	Scientifically unjustified.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	~ 238°C OC (Open cup).
Evaporation rate	No specific test data are available.
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Other flammability	No specific test data are available.
Vapour pressure	No specific test data are available.
Vapour density	No specific test data are available.
Relative density	No specific test data are available.
Bulk density	~ 0,89 @ 15 °C g/ml
Solubility(ies)	Hydrocarbons.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.

MAXIMUS SUPER DIESEL 20W-50

Viscosity	16,3-<21,9 cSt @ 100°C
Explosive properties	No specific test data are available.
Explosive under the influence of a flame	No specific test data are available.
Oxidising properties	Not known.
Comments	No specific test data are available.

9.2. Other information

Other information	No information required.
Refractive index	No specific test data are available.
Particle size	No specific test data are available.
Molecular weight	No specific test data are available.
Volatility	No specific test data are available.
Saturation concentration	No specific test data are available.
Critical temperature	No specific test data are available.
Volatile organic compound	No specific test data are available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising agents.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents. Strong acids. Inorganic halides. Strong alkalis.
--------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	In the event of incomplete combustion, smoke, carbon dioxide and carbon monoxide are formed. Bozunma sıcaklığına ısıldığında COx duman ve tahriş edici buharlarını salabilir.
----------------------------------	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	Based on available data the classification criteria are not met.
Other health effects	Based on available data the classification criteria are not met.
Acute toxicity - oral	
Summary	Based on available data the classification criteria are not met.

MAXIMUS SUPER DIESEL 20W-50

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u>	
Summary	Based on available data the classification criteria are not met.
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - inhalation</u>	
Summary	Based on available data the classification criteria are not met.
Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Summary	Based on available data the classification criteria are not met.
Skin corrosion/irritation	Based on available data the classification criteria are not met.
Animal data	Based on available data the classification criteria are not met.
Human skin model test	Based on available data the classification criteria are not met.
Extreme pH	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Summary	Based on available data the classification criteria are not met.
Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Summary	Based on available data the classification criteria are not met.
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Summary	Based on available data the classification criteria are not met.
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Summary	Based on available data the classification criteria are not met.
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Summary	Based on available data the classification criteria are not met.
Carcinogenicity	Based on available data the classification criteria are not met.
Target organ for carcinogenicity	No specific target organs known.
IARC carcinogenicity	Not listed.
NTP carcinogenicity	Not listed.
<u>Reproductive toxicity</u>	
Summary	Based on available data the classification criteria are not met.
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.

MAXIMUS SUPER DIESEL 20W-50

Specific target organ toxicity - single exposure

Summary	Based on available data the classification criteria are not met.
STOT - single exposure	Based on available data the classification criteria are not met.
Target organs	No specific target organs known.

Specific target organ toxicity - repeated exposure

Summary	Based on available data the classification criteria are not met.
STOT - repeated exposure	Based on available data the classification criteria are not met.
Target organs	No specific target organs known.

Aspiration hazard

Summary	Based on available data the classification criteria are not met.
Aspiration hazard	Based on available data the classification criteria are not met.

Toxicokinetics	No other information known.
General information	No other information known.
Inhalation	No other information known.
Ingestion	No other information known.
Skin contact	No other information known.
Eye contact	No other information known.
Acute and chronic health hazards	No other information known.
Route of exposure	No other information known.
Target organs	No specific target organs known.
Medical symptoms	No other information known.
Medical considerations	No other information known.

Toxicological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral,

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal,

Carcinogenicity

Summary The base oils in the product content contain less than 3% DMSO according to IP 346.

Mineral Oil

Carcinogenicity

Summary The base oils in the product content contain less than 3% DMSO according to IP 346.

Specific target organ toxicity - single exposure

MAXIMUS SUPER DIESEL 20W-50

STOT - single exposure If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. (Supplier information)

Aspiration hazard

Aspiration hazard Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs and death. (Supplier information)

Mineral oil (mixture)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀, 4h >5000 mg/m³, Inhalation, Rat

Calcium long chain alkylphenate sulphide

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Zinc dialkyl dithiophosphate

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 2230 mg/kg, Oral, Rat LD₅₀ 3100 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

Alkaryl amine

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

SECTION 12: Ecological information

Ecotoxicity May cause long lasting harmful effects to aquatic life.

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Ecotoxicity May be harmful to aquatic organisms. Spills form film layer on water surface and prevent oxygen transfer

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity

Summary No other information known.

MAXIMUS SUPER DIESEL 20W-50

Acute toxicity - fish	No other information known.
Acute toxicity - aquatic invertebrates	No other information known.
Acute toxicity - aquatic plants	No other information known.
Acute toxicity - microorganisms	No other information known.
Acute toxicity - terrestrial	No other information known.
<u>Chronic aquatic toxicity</u>	
Summary	May cause long lasting harmful effects to aquatic life.
Chronic toxicity - fish early life stage	No specific test data are available.
Short term toxicity - embryo and sac fry stages	No specific test data are available.
Chronic toxicity - aquatic invertebrates	No specific test data are available.
Toxicity to soil	No specific test data are available.
Toxicity to terrestrial plants	No specific test data are available.

Ecological information on ingredients.

Phenol-4-dodecyl

Acute aquatic toxicity

LE(C)₅₀ 0.01 < L(E)C₅₀ ≤ 0.1

M factor (Acute) 10

Chronic aquatic toxicity

M factor (Chronic) 10

12.2. Persistence and degradability

Persistence and degradability	No specific test data are available.
Phototransformation	No specific test data are available.
Stability (hydrolysis)	No specific test data are available.
Biodegradation	No specific test data are available.
Biological oxygen demand	No specific test data are available.
Chemical oxygen demand	No specific test data are available.

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Biodegradation Not expected to be readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential	No specific test data are available.
Partition coefficient	No specific test data are available.

MAXIMUS SUPER DIESEL 20W-50

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Bioaccumulative potential Potentially bioaccumulating.

12.4. Mobility in soil

Mobility	The product is immiscible with water and will spread on the water surface.
Adsorption/desorption coefficient	No specific test data are available.
Henry's law constant	No specific test data are available.
Surface tension	No specific test data are available.

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Mobility Liquid under most environmental conditions. Floats on water. If spread into ground the groundwater may be polluted.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

Other adverse effects No other information known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	The packaging must be empty (drop-free when inverted).
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Environmental Manager must be informed of all major spillages. Avoid the spillage or runoff entering drains, sewers or watercourses.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

MAXIMUS SUPER DIESEL 20W-50

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	T. C. Regulation on the Classification, Labeling and Packaging of Substances and Mixtures No. 28848, dated 11 December 2013, by the Ministry of Environment and Urbanization. According to Regulation (EC) No 1907/2006, Annex II, as amended.
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Safety Data Sheets for Substances and Preparations.
Health and environmental listings	Hazardous ingredients are listed.

15.2. Chemical safety assessment

SECTION 16: Other information

MAXIMUS SUPER DIESEL 20W-50

Abbreviations and acronyms used in the safety data sheet

E.U. : European union
 DMSO: Dimethyl sulfoxide
 KKE: Personal protective equipment
 STEL: Short term exposure limit
 T.C. : Republic of Turkey
 TWA: Workplace exposure limits
 UZEM: National Poison Information Center
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 GHS: Globally Harmonized System.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 PBT: Persistent, Bioaccumulative and Toxic substance.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 vPvB: Very Persistent and Very Bioaccumulative.
 IARC: International Agency for Research on Cancer.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 EC₅₀: 50% of maximal Effective Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.

Classification abbreviations and acronyms

Asp. Tox. = Aspiration hazard
 Skin Corr. = Skin corrosion
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)
 Eye Dam. = Serious eye damage
 Repr. = Reproductive toxicity

General information

This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters. Uses and Restrictions : This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. MSDS Distribution : The information in this document should be made available to all who may handle the product. Disclaimer : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Only trained personnel should use this material.

Key literature references and sources for data

This SDS is prepared based on the information received from raw material suppliers.

Classification procedures according to Regulation (EC) 1272/2008

Aquatic Chronic 4 - H413: Calculation method., Supplier information

MAXIMUS SUPER DIESEL 20W-50

Training advice	Untrained personnel should not use.
Revision comments	Revised classification.
Issued by	Sevda ŞAHAN Certified Safety Data Sheet Preparer (Certificate Id:GBF01.23.08;Dates: 03.11.2018-03.11.2021)
Revision date	16/09/2020
Revision	3
Supersedes date	13/06/2011
SDS number	10389
Hazard statements in full	H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H360 May damage fertility or the unborn child if swallowed. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.