

HIZAR-2T

Two-Cycle Engine Oil

Description

It is a mineral-based two-stroke engine oil formulated with high-performance additive technology, developed to meet the lubrication requirements of small, air-cooled two-stroke engines.

Applications

Suitable for use in air-cooled, two-stroke engines with displacements of less than 50 cc. It is used by mixing with gasoline in chainsaws, lawnmowers, and similar small-engine equipment. Unless a different mixing ratio is specified by the manufacturer, a dilution ratio of 1:20 (1 part oil to 20 parts gasoline) is recommended. The equipment or engine manufacturer's operating instructions should be referred to for the appropriate mixing ratio.

Benefits

- Facilitates easy starting and ignition with its excellent low-temperature lubrication properties.
- High viscosity index ensures complete protection both during cold starts and at high operating temperatures
- Protects pistons and piston rings against wear by forming a strong, durable oil film.
- Keeps the engine clean by preventing sludge and deposit formation through active cleansing agents in its formulation

Performance

API TC

Typical Specifications *

Density, 15 °C, kg/ m ³	ASTM D4052	0,887
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	71,40
Viscosity, 100 °C, mm ² /s		10,90
Viscosity Index	ASTM D2270	143
Pour Point, °C	ASTM D97	-15

* Values shown may differ between productions.

Hizar-2T



Petrol Ofisi