

MAXIMA VSA 5W-30

Fully Synthetic Motor Oil



Description

Fully synthetic motor oil designed for use in new generation and high technology passenger cars. It is formulated especially for gasoline and diesel vehicles of VW, Audi, Skoda and Seat. Due to its Low SAPS technology. It lengthens diesel particle filter's life and it minimizes harmful emission to the environment.

Applications

Recommended for new generation both for gasoline and diesel engines. Used in engines demanding VW 504 00/507 00 approval. Recommended for all driving conditions.

Benefits

- Thanks to its Low SAPS technology, it minimizes particles in the particle filter and decreases wear on the catalytic convertor in gasoline engines.
- Decreases oil consumption by minimizing vaporization.
- Provides maximum engine protection.
- Provides excellent wear protection.
- Offers stable performance during the operating time.

Performance

ACEA C3, VW 504 00/507 00, Porsche C30

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,850
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	66,7
Viscosity, 100 °C, mm ² /s		11,30
Viscosity Index	ASTM D2270	171
Pour Point, °C	ASTM D97	-48

* Values shown may differ between productions.

VSA 5W-30

