MAXIMOTO 10W-40 SCOOTER

Four-Stroke, Synthetic Motorcycle Oil

Description

Maximoto 10W-40 Scooter is a synthetic motor oil and it is formulated using synthetic technology that ensures excellent protection and performance.

Applications

Developed for next generation Scooter-type motorcycles using four-stroke automatic transmission. In addition, it is also suitable for use in motorcycles manufactured in Europe and Japan, for which compliance with API SN and JASO MB specifications are recommended.

Benefits

- Minimizes friction loss thanks to excellent lubrication at high revolutions and high temperatures;
- Extends the economic life of the motor by protecting it under all conditions;
- Ensures fuel economy;
- Thanks to its special formulation, ensuring better power transmission and softer gear shifting effect, it ensures high performance and comfortable driving in local traffic situations where frequent start-stop transmission is under way.

Performance

APISN. JASO MB

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, 15 °C, kg/liter	ASTM D4052	0,870
Flash Point, COC, °C	ASTM D92	236
Viscosity, 40 °C, mm ² /s	ASTM D445	93,3
Viscosity, 100 °C, mm²/s		13,50
Viscosity Index	ASTM D2270	145
Pour Point, °C	ASTM D97	-33

^{*} Values shown may differ between productions.



