MAXIMA 5W-40

Fully Synthetic Motor Oil

Description

Fully synthetic multi-grade engine oil which is blended from a combination of high-tech base oil and high performance additives.

Applications

Suitable for all diesel engines in the passenger cars and light commercial vehicles demanding SAE 5W-40 viscosity grade and ACEA A3/B4 engine oil performance level.

Benefits

- Provides maximum fuel economy, keeps engine clean.
- Extends oil change interval.
- Provides best fuel efficiency and increases engine efficiency.
- Contributes to high motor performance by reducing friction.
- Provides excellent oxidation resistance.

Performance

API SP/CF, ACEA A3/B4, RN 0700/RN 0710, MB-APPROVAL 229.5, VW 502 00/505 00, FIAT 9.55535-N2, PSA B71 2296

Typical Specifications*

SAE Viscosity Grade		5W-40
Density, 15 °C, kg/liter	ASTM D4052	0,854
Flash Point, COC, °C	ASTM D92	232
Viscosity, 40 °C, mm²/s	ASTM D445	77
Viscosity, 100 °C, mm²/s		12,80
Viscosity Index	ASTM D2270	169
Pour Point, °C	ASTM D97	-39

* Values shown may differ between productions.

5W-40

Petrol Ofisi Maxima Adapts to Every Challenge!