

MAXIMUS HD 10W-30

Fully Synthetic Heavy Duty Diesel Engine Oil



Description

Engine oil formulated with advanced technology additives and premium quality synthetic base oils, developed for Euro 5 and Euro 6 vehicles.

Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines. It is convenient for engines with and without DPF and engines with EGR and SCR. It is especially recommended for modern Volvo Heavy Duty engines.

Benefits

- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Reduces fuel consumption and extends drain intervals.
- Achieves piston cleanness by reducing piston deposit and residue.
- Protects the environment by exhaust emission control.

Performance

API CK-4/SN, ACEA E7/E9, DTFR 15C100 (MB 228.31), Volvo VDS-4.5, RENAULT Trucks RLD-4, Mack EO-S-4.5, MAN M3775, Cummins CES 20086/87, Ford WSS-M2C171-F1, CAT ECF-3/ECF-2/ECF-1-a, Detroit Diesel DFS 93K222, Deutz DQC III-18 LA, MTU Type 2.1, JASO DH-2

Typical Specifications*

SAE Viscosity Grade		10W-30
Density, 15 °C, kg/liter	ASTM D4052	0,866
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	75
Viscosity, 100 °C, mm ² /s		11,90
Viscosity Index	ASTM D2270	153
Pour Point, °C	ASTM D97	-39

* Values shown may differ between productions.

HD 10W-30

