

# COMPRESSOR OIL XT SERIES

High Performance, Mineral Based, Zinc -Free Compressor Oils

## Description

Mineral based oil for reciprocating and rotary screw type air compressors. Meets the requirements of the leading compressor manufacturers. Compatible with the sealing elements used in compressors.

## Applications

Specially designed for reciprocating and rotary screw type air compressors.

## Benefits

- Ensures great demulsibility and water separability.
- Performs superior thermal and oxidation resistance.
- Provides smooth operation at elevated temperatures for the compressors and prevents formation of residue and viscosity changes.
- Minimizes oil consumption by its low evaporation loss.
- Protects the compressors against rust and wear.
- Extends the service life of filter elements.
- Extends oil change interval (up to 4000 hours)

## Performance

DIN 51506 Type VDL, DIN 54506 Type VBL, DIN 51517-1 Type C, DIN 51517-2 Type CL

## Typical Specifications\*

ISO Viscosity Grade		32	46	68	100
Density, 5 °C, kg/liter	ASTM4052	0,870	0,881	0,880	0,890
Flash Point, COC, °C	ASTM D92/93	>210	>220	>230	>240
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	32	46	68	100
Viscosity Index	ASTM D2270	102	101	100	98
Pour Point, °C	ASTM D97	-30	-27	-24	-21

\* Values shown may differ between productions.



**Petrol Ofisi**