



SAFETY DATA SHEET MAXIMUS 10W40

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MAXIMUS 10W40

Product number 11342

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

Uses advised against This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. This product is designed only to suit automotive applications and no provision is made for the requirements of aviation applications.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFİSİ A.Ş.
Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ İstanbul
Tel: +90 850 339 1919
Fax: +90 216 275 3854
madeniyag@petrolofisi.com.tr

Contact person Customer Services: madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Customer Services: 0850 339 1919 (working hours)

National emergency telephone number Emergency Medical Services: 112 National Poison Consultance Center: 114

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

MAXIMUS 10W40

Hazard statements	H317 May cause an allergic skin reaction.
Precautionary statements	P261 Avoid breathing vapour/ spray. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label). P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Kalsiyum uzun zincirli alkaril sülfonat, Kalsiyum uzun zincirli alkaril sülfonat

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Distillates (petroleum), hydrotreated heavy paraffinic (Nota L, -R45, <3% dimethyl sulfoxide)	40-60%
CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-2119484627-25-0033	
Classification Asp. Tox. 1 - H304	
Distillates (petroleum), hydrotreated heavy paraffinic	25-40%
CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-2119484627-25-0033	
Classification Not Classified	
polyolefin polyamine succinimide, polyol	1-5%
CAS number: —	
Classification Aquatic Chronic 4 - H413	
Calcium long chain alkaryl sulfonate	1-5%
CAS number: 722503-69-7	
Classification Skin Sens. 1B - H317 Aquatic Chronic 4 - H413	

MAXIMUS 10W40

Calcium long chain alkaryl sulfonate	1-5%
CAS number: —	
Classification	
Aquatic Chronic 4 - H413	
Zinc alkyl dithiophosphate	1-5%
CAS number: 68649-42-3	
Classification	
Aquatic Chronic 2 - H411	
Calcium long chain alkaryl sulfonate	<1%
CAS number: 722503-68-6	
Classification	
Skin Sens. 1B - H317 Aquatic Chronic 4 - H413	
polyolefin polyamine succinimide, borate	<1%
CAS number: —	
Classification	
Aquatic Chronic 4 - H413	

The full text for all hazard statements is displayed in Section 16.

Composition comments The DMSO contents of some substances are classified by the manufacturer as <3% according to IP 346.

Ingredient notes See Section 8 for occupational exposure limits. The data complies the last T.C. and E.U. regulations.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	First aid personnel should wear appropriate protective equipment during any rescue.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Ingestion	Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Wash clothing and clean shoes thoroughly before reuse. In case of hot materials come into contact with the skin, immediately cool in water. Get medical attention if burns occur. In case of developing any sensitivity, medical assistance should be obtained.
Eye contact	Remove your lenses if they are present and can be removed. Wash your eyes with plenty of water, with opening and closing your eyelids. Get immediate medical attention. In case of hot material contact with eyes, immediately flush eyes with clear water for 15 minutes, keeping your eyelids open. Remove contact lenses if they are present and can be removed. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

MAXIMUS 10W40

General information	See Section 11 for additional information on health hazards. Treat symptomatically.
Inhalation	Prolonged or repeated inhalation by air may cause respiratory tract irritation or pulmonary effects. Symptoms of respiratory tract irritation may include coughing and difficulty in breathing.
Ingestion	Harmful: may cause lung damage if swallowed. Do not induce vomiting due to the risk of obstruction the respiratory tracts.
Skin contact	The product contains a sensitising substance. Skin contact may cause allergic skin reactions. Repeated skin contact may cause irritation. Symptoms may include pain, itching, bruising, bloating and swelling. Thermal burns may occur in contact with the skin when heated.
Eye contact	Long-term or serious eye irritation is not expected. Thermal burns may occur if this material is heated and eye contact.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific treatment. Treat symptomatically.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water, foam, dry chemical, carbon dioxide can be used to extinguish the flames.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide, oxides of sulfur, and unidentified organic and inorganic compounds. Oxides of following substances may occur as a result of combustion: Boron, phosphorus, calcium, zinc, nitrogen.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Oxides of sulphur. Unidentified organic or inorganic compounds. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting This product is flammable even if it is not easily ignited. Refer to Section 7 for proper handling and storage. Dispose of fire debris and contaminated fire-fighting water in accordance with applicable legal legislation. No action shall be taken without appropriate training or involving any personal risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use special protective clothing. Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure procedures and training for emergency decontamination and disposal are in place. Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Do not touch or walk into spilled material. Avoid inhalation of vapours and contact with skin and eyes. Do not enter storage areas or confined spaces unless adequately ventilated. Use suitable respiratory protection if ventilation is inadequate. For personal protection, see Section 8.

For non-emergency personnel Necessary precautions should be taken to ensure that non-educated personnel do not intervene.

MAXIMUS 10W40

For emergency responders Stop the leakage source if it can be done without risk. Limit spillage to prevent further contamination of soil, surface or ground water. Remove any spilled material as soon as possible by following the precautions in the section Exposure Controls / Personal Protection. Use suitable techniques such as non-flammable absorbent materials or pumping. When possible or appropriate, remove the contaminated soil from the area. Place contaminated products in disposable boxes and dispose of in accordance with regulations. If a heated material is spilled, allow it to cool before handling with disposal methods. Notification: In case of spillage, notify the local authorities as appropriate or as necessary.

6.2. Environmental precautions

Environmental precautions Apply protective methods to prevent spilled material from entering into water sources, water channels, sewers and soil. Inform the authorities if the product has caused environmental pollution. Prevent uncontrolled spreading of the product to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. If leakage cannot be stopped, evacuate area. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Absorb spillage with oil-absorbing material. Collect spillage. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. When handling waste, the safety precautions applying to handling of the product should be considered. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. See Section 1 for emergency contact information. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions The recommended reheating medium is hot water or low pressure steam. In order to prevent the substance from deteriorating to form dangerous gases, it is important to ensure that the temperatures mentioned below are not exceeded while reheating. When sufficient engineering controls are applied temperatures between 80-85 ° C are appropriate for short-term operations of following applications, loading, unloading and mixing in line. Static hazard: Electrostatic charge may accumulate when working on it. Tying or grounding may be required to minimize this risk. Review all processes that have the potential to create and collect electrostatic charge and / or flammable atmospheres, and follow the relevant mitigation practices.

Advice on general occupational hygiene Persons susceptible to allergic reactions should not handle this product. Do not eat, drink or smoke when using this product. Do not smoke in work area. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

MAXIMUS 10W40

Storage precautions

Store in accordance with national regulations. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Keep only in the original container in a cool, well-ventilated place. Store away from incompatible materials (see Section 10). Keep away from oxidising materials, heat and flames. Protect from freezing and direct sunlight. The container is not designed to contain pressure. Do not apply pressure to discharge the container otherwise it may rupture with explosive force. Empty containers may contain product residue and it can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition. Containers should be drained completely and disposed of properly.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

Oil mist: TWA: 5 mg/m³ (ACGIH). In no case should this limit be exceeded or the local limit, if it is more restrictive.

Ingredient comments

Highly refined mineral oil (C15-50): ACGIH : TWA : 5 mg/m³ STEL: 10 mg/m³ Mineral oil: TWA 5mg/m³

DNEL

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic
 DNEL: 2,7 (8h) mg/m³ (long term inhalativ worker systemic)
 DNEL: 5,4 (8h) mg/m³ (long-term inhalativ worker local)
 DNEL: 1,2 (24h) mg/m³ (long-term inhalativ consumer local)
 DNEL: 0,74 (24h) mg/kg/d (long-term oral consumer systemic)
 DNEL: 1,0 (8h) mg/kg (long-term dermal worker systemic)

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

When determining engineering controls and when choosing personal protection equipment, consider the possible risks of this substance (see Section 2), appropriate exposure limits, business activities and other substances in the workplace. If engineering controls and work practices are not sufficient to prevent exposure to harmful levels of this substance, the use of personal protective equipment as described in this section is recommended. Well-ventilated area.

Eye/face protection

Normally, eye protection equipment is not required. Wear side goggles for safe operation when a risk of splashing is possible. If this material is heated, use chemical goggles, protective goggles or face shield. (EN 166)

Hand protection

Use appropriate protective clothing to prevent skin contact. Protective clothing to be selected according to the procedures to be performed include gloves, aprons, boots and all the face protective materials. Wear insulated clothing to prevent skin contact if this material is heated or if engineering controls or work practices are not sufficient to prevent skin contact. Use nitrile rubber gloves. (EN 374) Protective work clothing must comply with DIN EN 13034.

Other skin and body protection

Avoid contact with skin. Wear appropriate clothing to prevent repeated or prolonged skin contact.

MAXIMUS 10W40

Hygiene measures	Persons susceptible to allergic reactions should not handle this product. Wash promptly with soap and water if skin becomes contaminated. Take off immediately all contaminated clothing and wash it before reuse. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.
Respiratory protection	Respiratory protection is not normally required.If user processes generate oil mist: 1)Havadaki konsantrasyonların hidrojen sülfid için mesleki maruz kalma sınırının altında olup olmadığını belirleyin.If not, use an approved respirator that provides adequate protection against the measured concentrations of this substance.Use a particulate cartridge in air cleaner breathing apparatus. 2)Determine if the concentrations in the air are below the mineral oil mist exposure limits.If not, use a pre-filter and a suitable respirator with an organic vapor cartridge.
Thermal hazards	If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Brownish.
Odour	Characteristic.
Odour threshold	No information available.
pH	Scientifically unjustified.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	230°C Cleveland open cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	Inconclusive data.

MAXIMUS 10W40

Decomposition Temperature	Inconclusive data.
Viscosity	100 °C : 13,5 cSt 40°C : 87,9 cSt
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	No suitable data is available.
Oxidising properties	No data available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	No information required.
Saturation concentration	No information available.
Critical temperature	No information required.
Volatile organic compound	No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	It can react with strong oxidizing chemicals such as strong acids or chlorate, nitrate, peroxide, etc.
-------------------	--

10.2. Chemical stability

Stability	This material is considered stable under normal environmental conditions and in the conditions of storage and handling foreseen.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No hazardous reaction under normal conditions of storage and use.
---	---

10.4. Conditions to avoid

Conditions to avoid	High temperature, spark and open flames. Static electricity and formation of sparks must be prevented. Excessive situations deviating from specified handling and storage conditions. Do not expose to direct sunlight.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
---------------------------	--------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Hydrogen sulphide (H ₂ S). Alkyl mercaptans. Methacrylates. Oil vapors in case of overheating. Carbon dioxide (CO ₂). Carbon monoxide (CO).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

MAXIMUS 10W40

Toxicological effects	Eye Irritation: Danger of eye irritation, based on evaluation of data from similar products. These data, indicates that a component contained in this product protects (or reduce the effect of irritation) against eye irritation. (ZnDTP)
<u>Acute toxicity - oral</u>	
Summary	LD50/LC50 values: 64742-54-7 distillates (petroleum), hydrotreated heavy paraffinic: > 5000 mg/kg (rat) (OECD 401) API (1982a) 64742-54-7 distillates (petroleum), hydrotreated heavy paraffinic: LOAEL: 125 mg/kg/d (rat) Mineral oil: LD50 (mouse) : >2000 mg/kg
Notes (oral LD₅₀)	Supplier's information.
<u>Acute toxicity - dermal</u>	
Summary	Distillates (petroleum), hydrotreated heavy paraffinic : LD 50: (rabbit) : > 2000 mg/kg Distillates (petroleum), hydrotreated heavy paraffinic : LD 50: (rabbit) : > 5000 mg/kg (OECD 402) API (1982a)
Notes (dermal LD₅₀)	Supplier's information.
<u>Acute toxicity - inhalation</u>	
Summary	64742-54-7: Distillates (petroleum), hydrotreated heavy paraffinic : LC50/4h : 5,53 mg/L (rat) (OECD 403), Exxon Biomedical Sciences, Inc. (1988a)
Notes (inhalation LC₅₀)	Supplier's information.
<u>Skin corrosion/irritation</u>	
Summary	In case of frequent and / or often contact with skin, irritation symptoms may occur.
<u>Serious eye damage/irritation</u>	
Summary	Eye contact may cause irritation.
<u>Respiratory sensitisation</u>	
Summary	Mist may cause slight irritation if inhaled.
<u>Skin sensitisation</u>	
Summary	Based on the available data, the product is not expected to have a skin sensitizing effect.
<u>Germ cell mutagenicity</u>	
Summary	It is not expected to cause genetic damage in the light of current data.
<u>Carcinogenicity</u>	
Summary	There is no test data about the carcinogenicity of this product. This product mainly consists of mineral based base oils. The base oils in this product are refined. The base oils in the product content contain less than 3% DMSO according to IP 346. Some of the inputs in this oil are: Not listed in the annual report of the National Toxicology Program (NTP) and it is not classified by the National Cancer Research Organization (IACR) as a carcinogenic substance for people (Group I), as a likely carcinogenic substance for humans (Group 2A) or as a probable carcinogenic material for people (Group 2B). Some of the inputs in this oil are not classified by the American Conference on Official Industrial Hygienists (ACGIH) as follows: approved on human carcinogens (A1), human carcinogenic effects suspected (A2), or unknown to humans but carcinogenic effects on animals (A3).
<u>Reproductive toxicity</u>	
Summary	There is no test data indicating that this product has a toxic effect on the reproductive system.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No specific test data are available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No specific test data are available.

MAXIMUS 10W40

Aspiration hazard

Aspiration hazard May be fatal if swallowed and penetrates into the respiratory tract.

Toxicokinetics No information is required.

SECTION 12: Ecological information

Ecotoxicity May be harmful to aquatic organisms. Spills form film layer on water surface and prevent oxygen transfer

12.1. Toxicity

Acute aquatic toxicity

Summary

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic: LL50 >100 mg/L (algae) LL50>100 mg/L (fishes) LL50> 10000 (24h) mg/L (gammarus pulex) (OECD 202) LL50> 100 (96h) mg/L (pimephales promelas) (OECD 203) EL50>10000 (24h) mg/L (daphnia magma) (OECD 202)

12.2. Persistence and degradability

Persistence and degradability There are not enough test data. It is not expected that the product may be readily biodegradable based on the ingredients of this product.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility This product floats on water. In the event of a spill, the product spreading to the ground may cause groundwater contamination.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Supplier data: This product does not contain PBT and vPvB.

12.6. Other adverse effects

Other adverse effects This product contains components that have a harmful effect on the aquatic environment. Do not allow to enter into soil, rivers or sewers.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Material Disposal: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. **Container Disposal :** Send to drum recoverer or metal reclaimer. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

SECTION 14: Transport information

MAXIMUS 10W40

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

Not applicable.

14.6. Special precautions for user

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	T. C. Environment and urban ministry, implementing Regulation on the Classification, Labeling and Packaging of Substances and Mixtures, No. 28848, dated December 11, 2013 T.C. Çalışma ve Sosyal Güvenlik Bakanlığı, 2 Temmuz 2013 tarihli, 28695 sayılı, Kişisel Koruyucu Donanımların İşyerlerinde Kullanılması Hakkında Yönetmelik. T. C. The Ministry of Labor and Social Security, Implementing Regulation on Health and Safety Measures for Working with Chemical Substances, numbered 28733 dated August 12, 2013 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Safety Data Sheets for Substances and Preparations.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

SECTION 16: Other information

MAXIMUS 10W40

Abbreviations and acronyms used in the safety data sheet	<p>E.U. : European union DMSO: Dimethyl sulfoxide UZEM: National Poison Information Center CAS: Chemical Abstracts Service. TWA: Workplace exposure limits STEL: Short term exposure limit DNEL: Derived No Effect Level. LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose). LC₅₀: Lethal Concentration to 50 % of a test population. LOAEL: Lowest Observed Adverse Effect Level. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.</p>
General information	<p>This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters. Uses and Restrictions : This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. Disclaimer : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.</p>
Key literature references and sources for data	<p>This SDS is prepared based on the information received from raw material suppliers.</p>
Issued by	<p>Sevda ŞAHAN Certified Safety Data Sheet Preparer (Certificate Id:GBF01.23.08;Dates: 03.11.2018-03.11.2021)</p>
Revision	<p>1</p>
Supersedes date	<p>28/01/2019</p>
SDS number	<p>20498</p>
Hazard statements in full	<p>H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.