

MAXIMA XT 10W-40

High Performance, Synthetic Motor Oil

Description

A synthetic motor oil for gasoline engines at API SL/CF and ACEA A3/B4 performance levels, formulated with high-tech synthetic base oils and performance additives. It protects the engine against wear at high temperatures and minimizes deposit formation.

Applications

It is recommended for all types of modern high performance vehicles, including passenger cars and gasoline engines with multi point fuel injection, as well as vehicles requiring oils at API SL/CF and ACEA A3/B4 performance levels.

Benefits

- Provides maximum fuel economy.
- Keeps engine clean.
- Ensures longer oil change intervals due to its high oxidation resistance.
- Enhances engine performance by reducing internal friction.
- Provides quick and full protection even during cold starts.
- Preserves its viscosity and forms maximum oil film under challenging working conditions.

Performance

API SL/CF

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, 15 °C, kg/liter	ASTM D4052	0,865
Flash Point, COC, °C	ASTM D92	244
Viscosity, 40 °C, mm ² /s	ASTM D445	95,76
Viscosity, 100 °C, mm ² /s		14,09
Viscosity Index	ASTM D2270	151
Pour Point, °C	ASTM D97	-36

* Values shown may differ between productions.

XT 10W-40

