

MAXIMUS 10W-30

Synthetic Diesel Engine Oil

Description

Synthetic diesel engine oil specially formulated with premium quality synthetic base oils and new generation performance additives to ensure excellent lubricating of new generation diesel engines operating under severe conditions.

Applications

Recommended for all applications involving light commercial vehicles, trucks, buses, construction machines and generators equipped with a diesel engine, especially with turbocharged and low emission diesel engines.

Benefits

- Maximizes engine performance and reduces maintenance cost by preventing excess wear.
- Contributes to fuel efficiency by reducing friction.
- Provides protection in wide range of temperature.
- Prevents sludge and cleans engine.

Performance

API CI-4, ACEA E7, DTFR 15B110 (MB 228.3), VOLVO VDS-3, RENAULT RLD-2, MACK EO-N, MAN 3275, CUMMINS CES 20077/20078, FORD WSS-M2C921-A, JASO DH-1, CAT ECF-1a/CAT ECF-2, DETROIT DIESEL DDC 93K215, Global DHD-1

Typical Specifications*

SAE Viscosity Grade		10W-30
Density, 15 °C, kg/liter	ASTM D4052	0,873
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	80
Viscosity, 100 °C, mm ² /s		11,80
Viscosity Index	ASTM D2270	141
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.

10W-30



Petrol Ofisi

Entrust your vehicle to Maximus, and keep moving forward!