MAXIMA DIESEL 5W-40

Fully Synthetic Motor Oil

Description

Fully sythetic multi-grade diesel engine oil which is blended from a combination of high-tech base oil and high performance additives.

Applications

Suitable for all diesel engines in the passenger cars and light commercial vehicles demanding SAE 5W-40 viscosity grade and ACEA A3/B4 engine oil performance level.

Benefits

- Provides maximum fuel economy, keeps engine clean.
- Extends oil change interval.
- Provides best fuel efficiency and increases engine efficiency.
- Contributes to high motor performance by reducing friction.
- Provides excellent oxidation resistance.

Performance

API SN/CF, ACEA A3/B4, VW 502.00/505.00, RN 700/710, MB 229.3

Typical Specifications*

SAE Viscosity Grade		5W-40
Density, 15 °C, kg/liter	ASTM D4052	0,860
Flash Point, COC, °C	ASTM D92	240
Viscosity, 40 °C, mm²/s	ASTM D445	77
Viscosity, 100 °C, mm²/s		12,80
Viscosity Index	ASTM D2270	169
Pour Point, °C	ASTM D97	-39

*** Values shown may differ between productions.**

Renewed Maxima with Adaptech technology provides full protection in all conditions.

Petrol Ofisi

Lubricants Customer Services | Phone: 0 (850) 339 19 19 Fax: 0 (216) 275 38 54 | E-mail: madeniyag@petrolofisi.com.tr