

MAXITRAK TRAKTÖR YAĞI 20W-50

Multigrade Tractor Oil

Description

High quality diesel engine oil developed specifically for turbo diesel engines of tractors and combine harvesters.

Applications

Used for turbo diesel engines of agricultural machines including the latest models.

Benefits

- Cleans the engine by preventing deposits with the help of detergent-dispersant additives.
- Helps preventing oil consumption and wear.
- Extends oil change intervals.
- Reduces product range in the filo by its wide application area.
- Helps engine to start easily in cold conditions, provides effective lubrication in hot conditions.
- Creates high film layer at high temperatures with its high Viscosity Index modifiers.

Performance

API CF-4/CF

Typical Specifications*

| | | |
|---------------------------------------|------------|--------|
| SAE Viscosity Grade | | 20W-50 |
| Density, 15 °C, kg/liter | ASTM D4052 | 0,890 |
| Flash Point, COC, °C | ASTM D92 | 260 |
| Viscosity, 40 °C, mm ² /s | ASTM D445 | 167 |
| Viscosity, 100 °C, mm ² /s | | 20 |
| Viscosity Index | ASTM D2270 | 136 |
| Pour Point, °C | ASTM D97 | -18 |

* Values shown may differ between productions.

20W-50

