

MAXIMUS HD-M 5W-30

Fully Synthetic Heavy Duty Diesel Engine Oil

Description

Ultra high performance engine oil formulated with advanced technology additives and premium quality synthetic base oils.

Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines produced after 2017 that requires DTFR 15C130. It is convenient for engines with and without DPF and engines with EGR and SCR. It is recommended to check OEM requirements for older generation vehicles.

Benefits

- Extends drain intervals.
- Enhances fuel efficiency with its low viscosity properties.
- Prevents oxidative thickening and wear.
- Compliant with bio-fuels.
- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Protects the environment by exhaust emission control.

Performance

API FA-4, DTFR 15C130, CUMMINS CES 20087, Detroit Diesel 93K223

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,855
Flash Point, COC, °C	ASTM D92	228
Viscosity, 40 °C, mm ² /s	ASTM D445	57,2
Viscosity, 100 °C, mm ² /s		9,97
Viscosity Index	ASTM D2270	162
Pour Point, °C	ASTM D97	-45

* Values shown may differ between productions.

HD-M 5W-30

