

MAXITRAK TMS OIL 500

High Performance Transmission and Hydraulic Oil

Description

Specially developed high performance transmission and hydraulic oil. Reduce clutch vibration and provides superior performance at low temperatures.

Applications

Used in hydraulics, transmissions and wet brakes of agricultural, construction and industrial vehicles. Meets the specifications of OEM manufacturers which recommend UTTO type lubricant.

Benefits

- Provides quiet operation in break systems, due to high performance additives to prevent friction.
- Extremely resistant against wear, oxidation and foaming.
- Ensures smooth power transmission.
- Prevents wear and break downs in transmissions, due to the new additive technology.
- Perfectly compatible with leak tightness elements and standard seal materials.
- Extends the equipment life and reduces maintenance costs.

Performance

API GL-4, Allis-Chalmers Power Fluid 821, AGCO-Allis Power Fluid 821XL, AGCO Massey-Ferguson M1135/M1141, Allison C-2, C-3 and C-4, Case International: MS-1204, 1205, 1206, 1207, Case-IH MS-1210, JIC 145 JI Case JIC 143 / 144, CNH Case/New Holland MAT 3525, CAT TO-2, Deutz-Allis 272843, 257541, 246634, ESNM2C41-B, ESN-M2C43, ESN-M2C48-A and ESN-M2C48-B, ESN-M2C53-A and ESN-M2C53-B, ESN M2C92-A, ESN-M2C134-A, B, C, D (Current), FNHA-2-C-201, Ford and New Holland FNHA-2-C-200A, Hesston-Fiat: (tractors only) AF-87, Multi-F, International Farmall MS-1204, JIC 185, International Harvester B-5, B-6 (International Harvester), John Deere: JDM J20A and J20B JDM J20C and J20D JDM J14B and J14C JDM J21A JDT 303 Quatrol, Komatsu Dresser: B-06-0001 and B-06-0002, Kubota: UDT (Current), Massey-Ferguson M-1110, M-1127A, and M-1127B, M-1129A, M-1135 (Current Worldwide), M-1141 (Current EP THF) M-1143 (Finished Oil) M-1145 (Finished Oil), MAT 3225 / Nexple fluid, 3525, 3526 (Current), Minneapolis-Moline Q-1766, Multi G 134/NH410B (FNHA-2-C-201), Multi-G (Current), New Idea Q-1802, New Holland (Fiat): FNHA-2-C-200, Oliver Q-1705, Type 55, Q-1722, Q-1766B, Renk Doromat: 873 874 A and 874 B (current), Sperry-Vickers 35VQ25 and M-2952-S (Vickers), I-286-S (Vickers), M-2950-S (Vickers), Steiger SEMS 17001 (Steiger), Versatile Specification 23M or 24M (Versatile), Volvo CE WB-101, White Farm Equipment Q-1826 (Current), ZF TE-ML 03E/03F/05E/05F/06K/17E/21F

Typical Specifications*

SAE Viscosity Grade		10W-30
Density, 15 °C, kg/liter	ASTM D4052	0,890
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	62
Viscosity, 100 °C, mm ² /s		9,70
Viscosity Index	ASTM D2270	140
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.

TMS 500

