

SUPER GRES MP-2

Lithium Thickener Automotive Grease

Description

Lithium thickener based multi-purpose grease for chassis and wheel bearings used in the automotive industry.

Applications

It is used for chassis lubrication requiring grease and medium speed rolling bearings carrying light and medium loads in automotive industry. Recommended for wheel hub of heavy duty vehicles and construction equipment. Suitable for use at temperature between -20 °C and 140 °C.

Benefits

- Provides extended protection for especially wheel bearings of all vehicles, due to its remarkable thermal stability.
- Ensures extended lubrication by sticking on the bearings with its high water resistance.
- Can be used in especially high performing passenger car due to its excellent surface adhesion.
- Protects bearings against rust and corrosion.
- Ensures long service life due to its high oxidation resistance.

Performance

DIN 51825 KP 2 N-20, TS 11584

Typical Specifications*

Thickener Type		Lithium
NLGI		2
Colour		Yellow
Base Oil Viscosity, 40 °C, mm ² /s	ASTM D445	220
Cone Penetration, 25 °C	ASTM D217	265-295
Timken OK, lb	ASTM D2509	50
Dropping Point, °C	ASTM D566	180
Welding Load, kg	ASTM D2596	315
Rust Test	ASTM D1743	Pass

* Values shown may differ between productions.

SÜPER GRES
MP-2

