

MAXIGEAR S 75W-80

Full Synthetic Long-Life Transmission Oil

Description

Maxigear S 75W-80 is a high performance, all seasons extreme pressure synthetic gear oil developed for buses and heavy duty vehicles with ZF gear box.

Applications

Maxigear S 75W-80 is developed for buses and commercial vehicles operating under extremely heavy duty, where particularly long oil change intervals are recommended, for use in ZF gear boxes with or without interarder systems.

Benefits

- Very good aging resistance provides a long life between oil changes.
- Very high protection against corrosion.
- Excellent lubrication and wear prevention.
- Super extreme pressure characteristics.
- Perfect temperature-viscosity compatibility ensured with the smart oil technology.
- Very low pour point reduces wear at initial operation, and provides fuel savings.

Performance

API GL-4, Eaton Europe (300,000 km or 3 years), DAF, Iveco, MAN 341 Type Z3/Z4, MIL-L-2105, Renault, Volvo 97307, ZF TE-ML 02L, TE-ML 16K

Typical Specifications*

SAE Viscosity Grade		75W-80
Density, 15 °C, kg/liter	ASTM D4052	0,860
Flash Point, COC, °C	ASTM D92	230
Viscosity, 40 °C, mm ² /s	ASTM D445	51,8
Viscosity, 100 °C, mm ² /s		8,90
Viscosity Index	ASTM D2270	153
Pour Point, °C	ASTM D97	-39

* Values shown may differ between productions.

S 75W-80



Petrol Ofisi