



SAFETY DATA SHEET MAXITRAK TMS OIL 500

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MAXITRAK TMS OIL 500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Transmission oil.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFİSİ A.Ş.
Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ İstanbul
Tel: +90 850 339 1919
Fax: +90 216 275 3854
madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Müşteri Hizmetleri: 0850 339 19 19 (mesai saatleri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Not Classified

Human health Prolonged skin contact may cause temporary irritation. Splashes in the eyes may cause redness and irritation.

Environmental The product is not expected to be hazardous to the environment.

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

MAXITRAK TMS OIL 500

Precautionary statements

P261 Avoid breathing vapour/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see medical advice on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Calcium branched chain alkaryl sulfonate

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50) CAS number: 74869-22-0 EC number: 278-012-2 See Section 8 for occupational exposure limits.	60-80%
Classification Not Classified	
değiştirilebilen nötr yağlar CAS number: —	1-5%
Classification Asp. Tox. 1 - H304	
Zinc alkyldithiophosphate CAS number: 68649-42-3 EC number: 272-028-3	1-5%
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	
Calcium long-chain alkaryl sulfonate CAS number: —	1-5%
Classification Skin Irrit. 2 - H315	

MAXITRAK TMS OIL 500

Calcium branched chain alkaryl sulfonate	1-5%
CAS number: —	EC number: 271-877-7
Classification Skin Sens. 1 - H317 Aquatic Chronic 4 - H413	

The full text for all hazard statements is displayed in Section 16.

Composition comments Some substances are not classified by legislation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use the following: Water.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

MAXITRAK TMS OIL 500

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)

None of the components has assigned exposure limits.

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50) (CAS: 74869-22-0)

Ingredient comments	There is no approximate limit value for this product. Steam, fog or smoke should be controlled to the lowest possible level.
Biological limit values	No information available.
DNEL	No information available.
DMEL	No information available.
PNEC	No information available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

MAXITRAK TMS OIL 500

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Yellow.
Flash point	224°C OC (Open cup).
Relative density	0,882 g/ml @ 15°C
Viscosity	10,4 cSt @ 100°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising agents.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.
-------------------	--

MAXITRAK TMS OIL 500

Ingestion	May cause discomfort if swallowed.
Skin contact	Liquid may irritate skin.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological information

Ecotoxicity	Not regarded as dangerous for the environment.
--------------------	--

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility	The product is immiscible with water and will spread on the water surface.
-----------------	--

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	---

SECTION 14: Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

MAXITRAK TMS OIL 500

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments	Revised classification.
Issued by	Emrah Parmak
Revision date	23/03/2016
Revision	2
Supersedes date	17/06/2011
SDS number	10387
Hazard statements in full	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.