

MAXIMA CX 0W-30 PLUS

Long Lasting Synthetic Motor Oil



Description

Next generation engine lubricating oil formulated by synthetic base oils and special additives, specially designed for motor vehicles fitted with emission reduction systems containing DPF and SCR.

Applications

Developed for vehicles that require a motor oil at the performance level of ACEA C2 and FIAT 9.55535-DS1/9.55535-GS1 in next-generation diesel and gasoline engines. It can also be used in vehicles requiring motor oil at the performance level of ACEA C3.

Benefits

- Provides product optimization in large vehicle fleets of different brands.
- Ensures high engine performance.
- Extends the life of exhaust emission systems.
- Protects the environment by contributing to low emission production.
- Helps keep the engine clean by reducing deposit and sediment formation.
- Supports fuel efficiency.

Performance

ACEA C2, Fiat 9.55535-DS1/GS1

Typical Specifications*

SAE Viscosity Grade		0W-30
Density, 15 °C, kg/liter	ASTM D4052	0,843
Flash Point, COC, °C	ASTM D92	238
Viscosity, 40 °C, mm ² /s	ASTM D445	55,6
Viscosity, 100 °C, mm ² /s		11,60
Viscosity Index	ASTM D2270	178
Pour Point, °C	ASTM D97	-42

**Values shown may differ between productions.*



Petrol Ofisi

Renewed Maxima with Adaptech technology provides full protection in all