

## MAXIMUS HD 15W-40

Ultra High Performance Diesel Engine Oil



### Description

Engine oil formulated with advanced technology additives and premium quality synthetic base oils, developed for Euro 5 and Euro 6 vehicles.

### Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines. It is convenient for engines with and without DPF and engines with EGR and SCR. It is especially recommended for modern Volvo Heavy Duty engines.

### Benefits

- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Reduces fuel consumption and extends drain intervals.
- Achieves piston cleanliness by reducing piston deposit and residue.
- Protects the environment by exhaust emission control.

### Performance

API CK-4/SN, ACEA E7/E9, DTFR 15C100, Volvo VDS 4.5, Renault RLD-3, Mack EOS 4.5, MAN M3775, Cummins CES 20086, Ford WSS-M2C171-F1, MTU Type 2.1, DDC93K222, CAT ECF-3, DEUTZ DQC III-18 LA

### Typical Specifications\*

SAE Viscosity Grade		15W-40
Density, 15 °C, kg/liter	ASTM D4052	0,876
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	113,4
Viscosity, 100 °C, mm <sup>2</sup> /s		14,70
Viscosity Index	ASTM D2270	133
Pour Point, °C	ASTM D97	-33

\* Values shown may differ between productions.

HD 15W-40

