

MAXIMA 0W-20

Fully Synthetic Motor Oil

Description

Maxima 0W-20 is produced based on synthetic lubrication technology to fulfill expectation of new high technology engines.

Applications

Maxima 0W-20 is recommended for the vehicles requiring special lubricants, designed specifically for improved engine performance, increased fuel efficiency and engine deposits.

Benefits

- Extends drain intervals far beyond those recommended for conventional oils.
- Maximizes energy efficiency for improved fuel economy.
- Maxima 0W-20 motor oil provides outstanding anti-wear protection with excellent viscosity film strength.
- Low-viscosity lubrication ensures improved engine performance through a wide range of temperatures.

Especially in cold weather, quick flow to critical parts will result in faster starts and better overall engine protection.

Performance

API SN/CF, ACEA A5/B5

Typical Specifications*

SAE Viscosity Grade		0W-20
Density, 15 °C, kg/liter	ASTM D4052	0,844
Flash Point, COC, °C	ASTM D92	228
Viscosity, 40 °C, mm ² /s	ASTM D445	45,5
Viscosity, 100 °C, mm ² /s		8,80
Viscosity Index	ASTM D2270	177
Pour Point, °C	ASTM D97	-42

* Values shown may differ between productions.

0W-20

